

LōDril® TR | LAD
DH | TRt



TR200

Bay Shore's powerhouse, the TR200 provides unmatched performance on the job with 200,000 ft-lbs of torque and 50,000 ft-lbs of crowd force, all directed with precision by our intuitive joystick controls. Key features include a 50,000 ft-lbs (max line pull) Kelly winch, compatibility with augers ranging from 18 inches to 14 feet in diameter, an impressive range of drilling depths (up to 100 feet), a crowd stroke of 228 inches per pass, and improved transportability with the option to disconnect the attachment from the carrier.



BAYSHORESYSTEMS.COM

sales@bayshoresystems.com | 844.644.3745



TR200



TR200 Specs

Rotary Torque (max)	200,000 ft-lbs 270 kN-m
Kelly Winch Line Pull (first layer, max)	50,000 lbs 222 kN
Hole Diameter (max, recommended) ¹	168 in 4,200 mm
Hole Diameter (min) ²	18 in 450 mm
Drill Speed Range (LHS) ³	30/60/100 RPM
Crowd Stroke	168 in 4,300 mm 228 in 5,800 mm
Hole Depth (max) ²	100 ft* 30 m*
Attachment Height ²	25-30 ft 7.6-9.1 m
Excavator Weight Class (x 1,000) ³	100-145 lbs 45-65 kg
Square Kelly Bars Includes	Dewatering holes, locking pins & chains
Kelly Elements - Square (max)	5
Round Locking Kelly Bars Includes	Dewatering holes & retention chains
Kelly Elements - RLK (max)	4

1 - Dependent on ground conditions, tooling and operation
 2 - Dependent on configuration
 3 - Excavator modifications may be required or anticipated

* Deeper depths are available, contact your sales representative for more information

TR SERIES Possibilities:

- Kelly bars round locking, square friction or both.
- High capacity on the kelly winch, improving productivity and faster cycle time.
- Boom modification and removable counterweight for reach, access plus stability.
- Single and multi-layer winch capabilities.
- Reaction jack for maximizing effective crowd force while maintaining compact footprint.
- The list goes on...

**Need more solutions?
 We'll custom engineer
 the right rig for you.**

BAYSHORESYSTEMS.COM
sales@bayshoresystems.com
844.644.3745