

LōDril[®] TR | LAD
DH | TRt



TR25

The TR25 boasts an impressive level of versatility while refusing to compromise on reliability or power. Its low profile, light weight, and intuitive controls make it easy to operate, and with its fully integrated Kelly winch and powerful rotary torque, the TR25 is guaranteed to take your projects to new depths. Designed to be the Swiss army knife of rigs, it will outperform the competition in a wide variety of conditions. No matter where the jobs takes you, the TR25 is up to the task.



BAYSHORESYSTEMS.COM

sales@bayshoresystems.com | 844.644.3745



TR25



TR25 Specs

| | |
|---|---|
| Rotary Torque (max) | 25,000 ft-lbs 35 kN-m |
| Kelly Winch Line Pull (first layer, max) | 15,000 lbs 67 kN |
| Hole Diameter (max, recommended) ¹ | 54 in 1,370 mm |
| Hole Diameter (min) ² | 18 in 450 mm |
| Drill Speed Range (LHS) ³ | 30/60/100 RPM |
| Crowd Stroke | 60 in 1,500 mm |
| | 72 in 1,800 mm |
| | 96 in 2,400 mm |
| | 140 in 3,600 mm |
| Hole Depth (max) ² | 80 ft 24 m |
| Attachment Height ² | 11-18 ft 3-5 m |
| Excavator Weight Class (x 1,000) ³ | 35-50 lbs 15-25 kg |
| Square Kelly Bars Includes | Dewatering holes, locking pins & chains |
| Kelly Elements - Square (max) | 8 |
| Round Locking Kelly Bars Includes | Dewatering holes & retention chains |
| Kelly Elements - RLK (max) | 5 |

* With upgrade

1 - Dependent on ground conditions, tooling and operation

2 - Dependent on configuration

3 - Excavator modifications may be required or anticipated

TR SERIES Possibilities:

- Kelly bars round locking, square friction or both.
- High capacity on the kelly winch, improving productivity and faster cycle time.
- Boom modification and removable counterweight for reach, access plus stability.
- Single and multi-layer winch capabilities.
- Reaction jack for maximizing effective crowd force while maintaining compact footprint.
- The list goes on...

**Need more solutions?
We'll custom engineer
the right rig for you.**

BAYSHORESYSTEMS.COM

sales@bayshoresystems.com

844.644.3745